

	1	2	3	4	5	6	7																																																																							
A	No.28AWG 7x0.127 Thinned Stranded Copper Conductor								A																																																																					
B	<div></div>								B																																																																					
C									C																																																																					
D									D																																																																					
E	<div><table><tr><th colspan="2">Color Orientation</th></tr><tr><td>#1</td><td>brown</td></tr><tr><td>#2</td><td>red</td></tr><tr><td>#3</td><td>pink</td></tr><tr><td>#4</td><td>yellow</td></tr><tr><td>#5</td><td>green</td></tr><tr><td>#6</td><td>blue</td></tr><tr><td>#7</td><td>purple</td></tr><tr><td>#8</td><td>gray</td></tr><tr><td>#9</td><td>white</td></tr><tr><td>#10</td><td>black</td></tr></table></div>	Color Orientation		#1	brown	#2	red	#3	pink	#4	yellow	#5	green	#6	blue	#7	purple	#8	gray	#9	white	#10	black	<div>Material:<ul style="list-style-type: none">• Voltage rating: 300V• Temperature rating: 105°C• Dielectric Strength: 2.0KV 60Hz 1 minute• Conductor resistance: 237/Km max.• Insulation resistance: 100M /M min. @500V DC• Tensile strength before aging: 1,500 PSI• Tensile strength after aging: 70% min. (136°C*168H)• Elongation before aging: 100% min.• Elongation after aging: 65% min. (136°C*168H)• Deformation test 50% max. (121°C*1H)• Cold bend test: -10°C*4H No cracking• Horizontal flame test: VW-1• UL Style: 2651-VW-1</div>						E																																																
Color Orientation																																																																														
#1	brown																																																																													
#2	red																																																																													
#3	pink																																																																													
#4	yellow																																																																													
#5	green																																																																													
#6	blue																																																																													
#7	purple																																																																													
#8	gray																																																																													
#9	white																																																																													
#10	black																																																																													
F									F																																																																					
G	<div>Unit: mm</div> <div><div>RoHS</div><div>Compliant</div></div>		<table><tr><td>Scale</td><td>1:1</td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td rowspan="2">Title Flat Ribbon cable - Multicolor 1.27mm Pitch, 300 feet-13" reel</td></tr><tr><td colspan="2">TOLERANCE</td><td></td><td></td><td></td><td></td><td>Drawn</td><td>15.05.14</td><td>Wilson</td></tr><tr><td>X.X</td><td>±0.40</td><td></td><td></td><td></td><td></td><td rowspan="2">Approved</td><td rowspan="2">15.05.14</td><td rowspan="2">Groll</td></tr><tr><td>X.XX</td><td>±0.25</td><td></td><td></td><td></td><td></td></tr><tr><td>X.XXX</td><td>±0.15</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td><td colspan="2" rowspan="2"><div>ASSMANN</div><div>WSW components</div></td><td rowspan="2">Drawing-No.</td><td rowspan="2">rev01</td></tr><tr><td>X.°</td><td>±3°</td><td></td><td></td><td></td><td></td></tr><tr><td>X.X°</td><td>±X°</td><td>①</td><td>Added color orientation</td><td>02.09.14</td><td>Wilson</td><td colspan="2" rowspan="3">1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us</td><td rowspan="2">Replace</td><td rowspan="2">Sheet 1/1</td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td></tr></table>	Scale	1:1					Date	Name	Title Flat Ribbon cable - Multicolor 1.27mm Pitch, 300 feet-13" reel	TOLERANCE						Drawn	15.05.14	Wilson	X.X	±0.40					Approved	15.05.14	Groll	X.XX	±0.25					X.XXX	±0.15								DIM	TOL					<div>ASSMANN</div> <div>WSW components</div>		Drawing-No.	rev01	X.°	±3°					X.X°	±X°	①	Added color orientation	02.09.14	Wilson	1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us		Replace	Sheet 1/1	Angle	TOL	Id.	Modification	Date	Name	G
Scale	1:1					Date	Name	Title Flat Ribbon cable - Multicolor 1.27mm Pitch, 300 feet-13" reel																																																																						
TOLERANCE						Drawn	15.05.14		Wilson																																																																					
X.X	±0.40					Approved	15.05.14	Groll																																																																						
X.XX	±0.25																																																																													
X.XXX	±0.15																																																																													
DIM	TOL					<div>ASSMANN</div> <div>WSW components</div>		Drawing-No.	rev01																																																																					
X.°	±3°																																																																													
X.X°	±X°	①	Added color orientation	02.09.14	Wilson	1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us		Replace	Sheet 1/1																																																																					
Angle	TOL	Id.	Modification	Date	Name																																																																									
H									H																																																																					
	1	2	3	4	5	6	7																																																																							